

1. 2016-1

Circle or cross: "T" if True – "F" if False.

- T / F Principle of least privilege: programs, users and systems should be given unlimited privileges to perform their tasks.
- T / F Computer system objects may be hardware or software.
- T / F Breach of confidentiality involves unauthorized reading of data.
- T / F Breach of integrity involves preventing legitimate use of the system.
- T / F Breach of availability involves unauthorized destruction of data.
- T / F An attack is always malicious and never accidental.
- T / F Script kiddies are persons who write scripts or codes to crack into computers.

2. 2016-2

Circle or cross: "T" if True – "F" if False.

```
$ ls -al
total 12
drwxr-xr-x 3 demo demo 4096 Oct 17 17:05 .
drwxrwxrwt 8 root root 4096 Oct 17 17:04 ..
dr-x--x--x 2 demo demo 4096 Oct 17 17:06 tmp
```

- T / F All users can enter directory tmp/.
- T / F Only user demo can read directory tmp/.
- T / F A cyber breach occurs when someone accesses a database through an insufficiently secured network connection.
- T / F A physical breach occurs when an unauthorized person is able to physically access a piece of equipment.
- T / F "Security" is an internal problem. On the other hand, "protection" also requires consideration of the external environment.
- T / F A backdoor is a method of bypassing normal authentication.
- T / F A trojan horse is an example of a backdoor.
- T / F A Keylogger is the action of recording (covertly) a keyboard.

3. 2017-1

Circle or cross: "T" if True – "F" if False.

- T / F** Security is a mechanism for controlling processes or users to resources (Yakoob et. al.).
- T / F** Operating Systems automatically apply permissions to files and folder, however users can manually apply them too (Yakoob et. al.).
- T / F** Symmetric cryptography is much faster than asymmetric one.
- T / F** Protection is strictly an internal problem. On the other hand, security is strictly an external problem.
- T / F** The security mechanisms control access to a system. On the other hand, protection system prevents unauthorized access.
- T / F** The three aspects to a protection mechanism are authentication, authorization, and access enforcement.
- T / F** In GNU/Linux, users can be organized into groups, with a single Access Control List (ACL) for an entire group.
- T / F** Trojan horses are often computer games software infected with viruses.
- T / F** An access list is a list of objects and the operations allowed on those objects for each domain (OSC9).
- T / F** If users are allowed to perform their own I/O operation, system integrity will be guaranteed (OSC9).

C Programing	
001 /* 002 * (c) 2017 Rahmat M. Samik-Ibrahim 003 * This is free software. 004 * REV01 Thu Mar 30 17:32:33 WIB 2017 005 * START Thu Mar 30 12:13:58 WIB 2017 006 */ 007 008 #include <stdio.h>	010 int tambah(int ii, int jj) { 011 return ii + jj; 012 } 013 014 void main() { 015 int ii = 4; 016 printf("The return of tambah is %d\n", tambah(1,ii)); 017 }
Program Output (Line 016):	

4. 2017-2

Principle of least (01) dictates that programs, users, and even systems be given just enough privileges to perform their tasks (OSC9). (02) is strictly an internal problem (OSC9). (03) requires also consideration of the external environment within which the system operates (OSC9). A system is (04) if its resources are used and accessed as intended under all circumstances (OSC9). Security is often deployed for (05) against external threats (OSC9). Breach of (06) involves unauthorized reading of data (OSC9). Breach of (07) involves unauthorized modification of data (OSC9). Breach of (08) involves unauthorized destruction of data (OSC9). (09) of service involves unauthorized use of resources (OSC9).

(10) of service involves preventing legitimate use of the system (OSC9). (11) is when one participant in a communication pretends to be someone else (OSC9). In a session (12), an active communication session is intercepted (OSC9). A code segment that misuses its environment is called a (13) (OSC9). (14) are self-replicating and are designed to infect other programs (OSC9). A (15) is a process that uses the spawn mechanism to duplicate itself (OSC9). In a (16) encryption algorithm, the same key is used to encrypt and to decrypt (OSC9). In an (17) encryption algorithm, there are different encryption and decryption keys (OSC9). (18) are very useful in that they enable anyone to verify the authenticity of the message (OSC9). (19) is the ability of an individual or group to seclude themselves, or information about themselves, and thereby express themselves selectively (WIKI).

Match the number of the sentence above with these following phrases:

- | | | | |
|---|---------------------------------------|--|---------------------------------------|
| <input type="checkbox"/> Asymmetric | <input type="checkbox"/> Availability | <input type="checkbox"/> Confidentiality | <input type="checkbox"/> Denial |
| <input type="checkbox"/> Digital Signatures | <input type="checkbox"/> Hijacking | <input type="checkbox"/> Integrity | <input type="checkbox"/> Masquerading |
| <input type="checkbox"/> Privacy | <input type="checkbox"/> Privilege | <input type="checkbox"/> Protection | <input type="checkbox"/> Protection |
| <input type="checkbox"/> Secure | <input type="checkbox"/> Security | <input type="checkbox"/> Symmetric | <input type="checkbox"/> Theft |
| <input type="checkbox"/> Trojan Horse | <input type="checkbox"/> Viruses | <input type="checkbox"/> Worm | |

C Programing	
<pre>001 /* 002 * (c) 2017 Rahmat M. Samik-Ibrahim 003 * http://rahmatm.samik-ibrahim.vlsm.org/ 004 * This is free software. 005 * REV00 Mon Oct 16 21:15:03 WIB 2017 006 * START Mon Oct 16 21:15:03 WIB 2017 007 */ 008 009 #include <stdio.h> 010 011 char globalChar='a'; 012</pre>	<pre>013 char* getGlobal(void) { 014 char* charPTR=&globalChar; 015 printf("getGlobal1 %c\n", globalChar); 016 *charPTR='b'; 017 printf("getGlobal2 %c\n", *charPTR); 018 return charPTR; 019 } 020 021 void main (void) { 022 char localChar='c'; 023 printf("==== main1 %c\n", localChar); 024 localChar=*getGlobal(); 025 printf("==== main2 %c\n", localChar); 026 }</pre>

Program Output:

5. 2018-1

An (01) list is a list for each object consisting of the domains with a nonempty set of access rights for that object. A (02) list is a list of objects and the operations allowed on those objects for each domain. Proper access to the hardware is necessary for system (03). It will be difficult to (04) a system if users are allowed to access the hardware. The (05) principle is useful in limiting the amount of damage from a faulty process. Typically, a breach of confidentiality is the goal of an (06). Breach of integrity can result in passing of (07) to an innocent party. (08) is a common example of breach of availability. Theft of service involves (09) use of resources. (10) is not an attack but rather a means for a cracker to detect a systems vulnerabilities to attack.

Match the number of the sentence above with these following phrases:

- | | | | |
|---------------------------------------|---|--|-----------------------------------|
| <input type="checkbox"/> access | <input type="checkbox"/> capability | <input type="checkbox"/> integrity | <input type="checkbox"/> intruder |
| <input type="checkbox"/> liability | <input type="checkbox"/> need-to-know | <input type="checkbox"/> Port scanning | <input type="checkbox"/> protect |
| <input type="checkbox"/> unauthorized | <input type="checkbox"/> Website defacement | | |

What is the output of this following program:

```

001 /* (c) 2018 This is a free program */
002 /* Rahmat M. Samik-Ibrahim      */
003
004 #include <stdio.h>
005
006 void main(void) {
007     char string[]="HALLO";
008     printf("START\n");
009     printf("%s\n", string);
010     printf("%c\n", *string);
011     printf("%c\n", string[1]);
012     printf("STOP\n");
013 }
```

6. (6 points) 2018-2 (79%)

(01) is a measure of confidence that the integrity will be preserved. (02) is the set of access control mechanisms. A system is (03) if its resources are used and accessed as intended. A (04) resource can defend against use or misuse. A (05) is the potential for a security violation, whereas an (06) is an attempt to break security. (07) is when a participant in a communication pretends to be someone else. Mechanisms determine (08) something will be done; policies decide (09) will be done. A list of objects together with the operations allowed on those objects is known as (10) list.

Match the number of the sentence above with these following phrases:

- | | | | | |
|---|---|---|--|--|
| <input type="checkbox"/> attack (100%) | <input type="checkbox"/> capability (90%) | <input type="checkbox"/> how (90%) | <input type="checkbox"/> Masquerading (100%) | <input type="checkbox"/> protected (70%) |
| <input type="checkbox"/> Protection (70%) | <input type="checkbox"/> secure(60%) | <input type="checkbox"/> Security (70%) | <input type="checkbox"/> threat(100%) | <input type="checkbox"/> what(90%) |

What is the output of this following program (76%):

```
001 /* (c) 2018 This is free software *
002  * NOTE: ASCII 61H = a; 62H = b */
003 #include <stdio.h>
004 void main(void) {
005     unsigned int    ii='a';
006     unsigned char   ch='b';
007     unsigned char*  st="dcba";
008     printf("START\n");
009     printf(" ii    = %X or %c\n",  ii,  ii);
010     printf(" ch    = %X or %c\n",  ch,  ch);
011     printf("*st    = %X or %c\n",  *st, *st);
012     printf(" st[2] = %X or %c\n", st[2], st[2]);
013     printf("STOP\n");
014 }
```